

STRAIGHTLINE PERFORMANCE

121-198

2008-11 Ski-doo REV XP 800R 137" track 0-3000ft Clutch Kit

Recommended Settings:

Ramp Position # 2-3

Pin Weight: 21.3-22.4

Operating RPM – 7900-8200

The new QRS secondary clutch kit install.

1. Remove the chain case cover and un-bolt the top gear.
2. On the clutch side unbolt and remove the half moon keeper holding the jackshaft bearing into the chassis bearing support.
3. Place a screw driver or similar device in the bolt hole of the jackshaft from the chain case side and tap the entire jackshaft out. Have someone hold and lightly pull from the clutch side to completely remove the clutch and shaft assembly.
4. Use the Straightline helix and spring compressor to compress the helix. You may have to use light heat and an impact driver to remove the 4 stock bolts from the helix. After removing the helix install the plastic washer in the stock helix into the new SPI helix, and then install the spring. Be sure to lock tight the bolts back into the helix.
5. Re-install the clutch and jackshaft into the chassis; be sure not to loose the spacer behind the top sprocket. Bolt top gear back on and install bearing keeper support.
6. Remove primary clutch and install new spring and adjustable pin kit to proper specifications.
7. RPM's under acceleration will be 7900-8000 peak rpm's will be 8100-8200. It is not uncommon under **extremely** long pulls to see slightly higher rpm's.
8. **When installing the pin weight into pin use the supplied 1" long set screw to achieve the 22.4g setting. This pin is not on the direction sheet.**

This is a trail kit and designed to for all around use. If sled is under-revving at wide-open throttle, remove setscrews to achieve the next lower setting. If this sled over-revving install 1 gram at a time till desired rpm is achieved.

| Quantity | Item # | Descriptions | In Box |
|----------|---------|------------------------------------|--------|
| 1 | 121-149 | Primary Spring Gray 200-320lbs | |
| 3 | 121-125 | 412 Ramps | |
| 1 | 121-140 | Heavy Pin Kit | |
| 1 | SPI-20 | SPI-20 Helix | |
| 1 | 121-158 | Secondary Spring Orange 215-320lbs | |
| 1 | | Sticker | |

Checked and Packaged By

Technical questions please email tech@straightlineperformance.com



Facebook @ straightlineperformanceinc

Youtube @ straightlineperfinc

Twitter @ straightlineperf

Straightline Performance
15250 Hornsby St NE
Forest Lake, MN 55025 651-466-0212
www.straightlineperformance.com