



2016-18 Ski-Doo XR1200 High Performance Header
(Will not work with front mounted radiator)
134-170

Installation and Set-up Instructions

Straightline's Ski-doo 1200 performance header gains 6-7ft of torque and 10+hp peak at 8300 rpm's. The performance header is a direct bolt on and required no fuel programming. Fuel programming will increase acceleration and mid range performance, but is not required for peak rpm performance. No issues will occur without the fuel programming. In the front bulk head area remove the aluminum rivet toward the front of the frame, and replace with the supplied button head bolt and nylock nut. Do not remove the stock muffler; it must remain in place during the installation. When installing the header install the center tube first, this will help the other 2 tubes install easier. Using the supplied heat tape cover the air box and heater hose coming out of the engine underneath the header. Rap the air box just above the header with the head tape; be sure to also cover the straps that tie down the air box to the frame.



Aluminum rivet removed



Install supplied button head bolt and nylock nut

STRAIGHTLINE ***PERFORMANCE***

Technical Question Please Email Tech@straightlineperformance.com

Parts Included:

Qty	Part Number	Description	In Box
1	IT-134-170	1200 Header	
1	1173755	1/4" x 1" Bolt	
1	1170860	1/4" Nylock Nut	
3ft	XXXX	Heat Tape	
1		Sticker	
1		Instructions	

Checked By:	
-------------	--



Facebook @ straightlineperformanceinc

Youtube @ straightlineperfinc

Twitter @ straightlineperf

Straightline Performance 15250 Hornsby Rd Forest Lake, MN 55025 651-466-0212 www.straightlineperformance.com